

Order no.: 174836

**Mobile scaffolding 1.35 ×
2.45 m with chassis bar
and double platform
Platform height 8.58 m**

Accessories for the product family



Order no.: 027993

**Safety railing for
mobile scaffolding**



Order no.: 027901

**Push-fit frame
135/196**



Order no.: 027956

**Railing lengthwise
2,450 mm**



Order no.: 027910

**Platform with
trapdoor For
scaffolding length:
2.45 m**



Order no.: 027930

**Platform without
flap For scaffolding
length: 2.45 m**



Order no.: 027911

**Toe board front
side For scaffolding
width: 1.35 m**



Order no.: 027914

**Toe board long side
For scaffolding
length: 2.45 m**



Order no.: 027908

**Diagonal brace
2.45 m**



Order no.: 027907

**Horizontal strut For
scaffolding length:
2.45 m**



Order no.: 027923

Chassis bar 2 m



Order no.: 027917

Swivel castor with spindle height adjustable Ø 200 mm




Order no.: 027940

Step-on bracket



Order no.: 027912

Ballast weight with hanging brackets RAL 1021



Order no.: 019081

Clip tray for tubes Ø 50 mm



Order no.: 027920

Wall spacer adjustable up to 1.0 m



Order no.: 070506

Frame extension can be clamped on Adjustment range max. 400 mm



Order no.: 019274

Storage tray 500 x 220 mm Clamping range 38–51 mm



Order no.: 019276

Storage tray 800 x 300 mm Clamping range 38–51 mm



Order no.: 019175

Inspection sticker 40 x 40 mm



Order no.: 019176

Inventory sticker



Order no.: 070508

Safety door on front side Push-fit frame 1.35



Order no.: 070522

Scaffolding connector set For scaffolding width: 1.35 m



Order no.: 019136

Spring clip for mobile scaffolding with short pin, closed



Order no.: 070520

Scaffolding strut telescopic 2,120–3,400 mm



Order no.: 027104

Height-adjustable spindle



Order no.: 027922

Swivel castor with spindle, non-marking grey height adjustable Ø 200 mm



Order no.: 027921

Swivel castor with spindle, electrically conductive height adjustable Ø 200 mm



Order no.: 027958

Swivel castor Ø 200 mm With parking brake and pin



Order no.: 027902

Push-fit frame 135/112