



Order no.: 051204

Platform stairs, with  
double-sided access, with  
spring-loaded castors,  
steel grating



Number of steps

2x3

**2x4**

2x5

2x6

2x7

2x8

## Specification

Working height 3 m	Step design Steps	Number of steps/rungs 2x 4 steps	Platform included as step Yes	Step/Platform surface Steel grating
Non-slip class R10	Platform height 960 mm	Height 1.96 m	Platform length 800 mm	Platform width 600 mm
Step depth 200 mm	Step/Rung distance 240 mm	Inclination 60 °	Depth of side-rails 57 mm	Width of side-rails 24 mm
Castor diameter 125 mm	Base area length 1.79 m	Base area width 820 mm	Max. load capacity 150 kg	Design type Freestanding   Double-sided access   With castors
Transport dimensions (plus packaging) 1799 x 837 x 958 mm, 44.8 kg	Business division MUNK Günzburger Steigtechnik	Order no. 051204		

## Facts

- Aluminium platform stairs double-sided
- Stable rectangular tube side-rails
- Steps with a depth of 200 mm
- Roomy platform (600 x 800 mm)

- Railing on both sides and knee and toe board for safe stance (height: 1,000 mm)
- Four Ø 125 mm self-locking swivel castors, 2 with locking device
- Easy to assemble (delivered unassembled)
- In accordance with DIN EN 131-7, handrails are optional for ascending platform ladders with an ascent angle  $\geq 60^\circ$
- Available in various step and platform designs
- Maximum load: 150 kg

### Scope of supply

- Platform stairs: 1 x
- Swivel castor: 4 x
- Instructions for use and operation: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic

- No health hazards for the users

More product pictures

---



## Added value

### Safe working

- Handrails for safe ascent and descent
- Large-format, non-slip platforms
- Conical side-rail guide for safe stance
- Railings and knee boards for safe access and stance



### Castors

- Ergonomic and comfortable handling
- Simple movement from place to place



### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



### Sponsored by BG BAU

Specification subject to conditions; for the latest information please visit the BG BAU website (statutory accident insurance company for the construction and construction related services in Germany). Since 2014, the BG BAU has been promoting the purchase of platform ladders, step stools and ladder accessories with single-sided and double-sided access. All members of the BG BAU profit from this. This aims to prevent work accidents on building sites and improve ergonomic working practices. For more information by BG BAU, please visit:

[www.bgbau.de/service/angebote/arbeitsschutzpraemie](http://www.bgbau.de/service/angebote/arbeitsschutzpraemie)

A brief overview of the subsidy and an overview of our eligible products can be found on our website under [know-how](#).

## Certificates

---



5011053.24001 -  
Certificate Product  
Safety Type  
approved

Valid in

DIN EN 131-7:2013  
DIN EN 131-3:2018

## Corporate certifications

---

### Standards for quality and sustainability



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

