MUNK
Sicherheit. Made in Germany.



Order no.: 051102

Platform stairs, with single-sided access, with spring-loaded castors, steel grating

Number of steps

2 | 3 | 4 | 5 | 6 | 7 | 8

Specification

Working height 2.5 m	Step design Steps	Number of steps/rungs 2 steps	Platform included as step Yes	Step/Platform surface Steel grating
Non-slip class R10	Platform height 500 mm	Height 1.48 m	Platform length 800 mm	Platform width 600 mm
Step depth 200 mm	Step/Rung distance 240 mm	Inclination 60 °	Depth of side-rails 57 mm	Width of side-rails 24 mm
Castor diameter 125 mm	Base area length 1.07 m	Base area width 720 mm	Max. load capacity 150 kg	Design type Freestanding | Single-sided access | With castors
Transport dimensions (plus packaging) 1069 x 719 x 480 mm, 30.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 051102		

Facts

- Aluminium platform stairs, single-sided
- Stable rectangular tube side-rails
- Steps with a depth of 200 mm
- Roomy platform (600 x 800 mm)
- All-round railing on three sides (height 1000 mm) including knee rail and toe board for maximum fall protection
- Four Ø 125 mm self-locking swivel castors, 2 with locking device
- Easy to assemble (delivered unassembled)
- In accordance with DIN EN 131-7, handrails are optional for ascending platform ladders with an ascent angle ≥ 60°

- Available in various step and platform designs
- Maximum load: 150 kg

Scope of supply

- Platform stairs: 1 x
- Spring-loaded castor: 4 x
- Instructions for use and operation: 1 x

More product pictures



Added value

Safe working

- Handrails for safe ascent and descent
- Large-format, non-slip platforms
- Conical side-rail guide for safe stance
- Railings and knee boards for safe access and stance



Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Castors

- Ergonomic and comfortable handling
- Simple movement from place to place



Certificates



5011053.24001 -
Certificate Product
Safety Type approved

Valid in

DIN EN 131-7:2013
DIN EN 131-3:2018

Corporate certifications

Standards for quality and sustainability

