MUNK
Sicherheit. Made in Germany.



Order no.: 011300

ML folding scaffolding

Design type

Without telescopic outrigger

With telescopic outrigger

Specification

Working height 3 m	Scaffolding length 1.88 m	Scaffolding width 800 mm	Scaffolding height 1.88 m	Platform width 600 mm
Platform length 1.6 m	Load capacity 1.5 kN/m2	Max. load capacity 150 kg	Transport dimensions (plus packaging) 1710 x 805 x 238 mm, 18 kg	Business division MUNK Günzburger Steigtechnik
Platform height 1 m				

Facts

- Folding ladder scaffolding made of stable rectangular tube side-rails
- Folding frame with self-locking hinges
- Space-saving transport and storage
- For narrow passages in assembled condition thanks to a chassis bar width of 800 mm
- Four Ø 125 mm swivel castors with locking mechanisms
- Slip-resistant platform for secure standing

- Delivered in assemblies. Once assembled, the scaffolding can be quickly set up and dismantled without tools
- Optional telescopic outriggers for even greater stability
- Maximum load: 150 kg
- Additional side boards for intermediate platforms are available as an option for country-specific requirements (e.g. Austria and France)

More product pictures











Added value

Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools



Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application



Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant



Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs



Expand your scaffolding with a safety railing (SG) and ensure reliable protection at work thanks to the system-integrated side protection! The retrofit reduces the risk of falling and enables the BG BAU work safety subsidy to be paid for up to 50% of the purchase costs (max. 100 euro per measure).

✔ Suitable for this product: Compatible SG safety railings offer effective side protection and are easy to retrofit.

All members of the BG BAU profit from this subsidy. This is intended to prevent accidents at work and improve ergonomics, especially on construction sites. All information from BG BAU can be found at: www.bgbau.de/service/angebote/arbeitsschutzpraemie

A brief overview of the subsidy and an overview of our eligible products can be found on our website at Knowledge.

MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability









