



Order no.: 011416

Rung straight ladder 350 mm wide with standard stabiliser



Number of rungs

| 12 | 14 | 16 | 18 | 20 | 22 | 24 |
|----|----|----|----|----|----|----|
| | | | | | | |

Specification

| Working height 5.8 m | Step design Rungs | Number of steps/rungs 16 rungs | Step/Rung height 30 mm | Step depth 30 mm |
|------------------------------------------------------|-----------------------------------------------------------|-----------------------------------|--------------------------------|-------------------------------------------------------|
| Step/Rung distance 280 mm | Type of non-slip protection Aluminium corrugated | Ladder length 4.7 m | Outer width 350 mm | Stabiliser width 930 mm |
| Depth of side-rails 73 mm | Width of side-rails 24.5 mm | Max. load capacity 150 kg | Design type To lean against | Transport dimensions 4663 x 355 x 95 mm, 9.5 kg |
| Business division MUNK Günzburger Steigtechnik | Order no. 011416 | | | |

Facts

- Aluminium rung straight ladder
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Rung distance: 280 mm



- Ladder width: 350 mm
- Standard stabiliser with non-slip ladder shoes with optimum width for the selected product. Ensures maximum stability and safe ascent for straight ladders over 3.0 m. The stabiliser is enclosed separately and is screwed to the lower end of the rail in two places

Maximum load: 150 kg

Scope of supply

Ladder: 1 x

Stabiliser (enclosed separately): 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users



More product pictures





Added value

Standard stabiliser

Safe, standards-compliant ascent for straight ladders over 3.0 m

- Different stabiliser widths, suitable for the selected ladder length
- Non-slip ladder shoes
- Individually available as spare part



Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on <u>TRBS 2121 Part 2</u> has been summarised on our Service page
- Read our <u>tips and tricks</u> on how to calculate <u>working height</u>



roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down





Corporate certifications

Standards for quality and sustainability









