

Order no.: 012006

Rung window cleaner's
ladder middle section



Number of rungs

5



Specification

Ladder length 1.65 m	Number of steps/rungs 5 rungs	Step/Rung height 30 mm	Step depth 30 mm	Step/Rung distance 280 mm
Upper outer width 340 mm	Lower outer width 430 mm	Inclination 70 °	Depth of side-rails 73 mm	Width of side-rails 25 mm
Max. load capacity 120 kg	Design type To lean against	Transport dimensions 1712 x 445 x 95 mm, 3 kg	Business division MUNK Günzburger Steigtechnik	Order no. 012006

Facts

- Rung window cleaner's ladder made of aluminium
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged step-to-side-rail connection
- Secure push-fit connection with additional hook lock

- Upper ladder with castors and abrasion-resistant contact rubber pad with wedge cut-out
- Lower ladder with nivello® stabiliser for extra stability and safe ascent (enclosed separately)
- Depending on the selection, a maximum of four individual parts can be combined, as the standing height of 5.0 m must not be exceeded
- Rung distance: 280 mm
- Maximum load: 120 kg


Scope of supply

- Ladder middle section: 1 x
- Instructions for use and operation: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



clip-step R 13 step padding

Certified non-slip protection for step ladders

- Fulfills the requirements of the highest possible non-slip class R 13 thanks to aluminium oxide particles
- Improves work safety in wet and oil-contaminated environments
- Applied up to the maximum accessible step as a visual check
- Retrofittable, available as a spare part and also in yellow in selected lengths (RAL 1021)



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



The movable ladder shoe sets new standards in stability

[Learn more](#)



nivello® stabiliser

Extra safe, standards-compliant ascent for straight ladders over 3.0 m

- Extra wide stabiliser for even greater stability
- nivello® ladder shoes with patented 2-axis inclination technology, integrated work angle check and exchangeable foot plates
- Individually available as spare part



roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



Corporate certifications

Standards for quality and sustainability

