



Order no.: 061445

Access protection access ladder

Specification

Material Aluminium Transport dimensions 3145 x 425 x 105 mm, 6.5 kg Business division MUNK Günzburger Steigtechnik Order no. 061445

Facts

- Hang-in, lockable
- Length 3,140 mm
- Working length approx. 2,340 mm
- Suitable for climbing heights of 4.50 m and more
- Can be shortened by max. 2 rungs on site
- Distance from entrance level to lower edge of back protection min. 2,700 – max. 3,000 mm in accordance with DIN 18799-3

Scope of supply

Ladder: 1 x



Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning





Corporate certifications

on sustainability criteria

