



Order no.: 120036

Mobile container
breathing apparatus
boxes and spare
canisters

Type

- Breathing apparatus
- Breathing apparatus and spare bottles
- Breathing apparatus boxes
- Breathing apparatus boxes and spare bottles

Specification

Product type Atemschutzgeräteboxen und Ersatzflaschen	Length 1.2 m	Width 800 mm	Height 1.7 m	Max. load capacity 500 kg
Castor diameter 200 mm	Braking system Standard	Number of levels 3	Number of breathing apparatuses 6	Number of breathing apparatus cylinders 6
Transport dimensions (plus packaging) 1200 x 800 x 1697 mm, 140 kg	Business division MUNK Rettungstechnik	Order no. 120036		

Facts

- Mobile container with "standard" undercarriage
- For the safe and protected transport of six breathing apparatuses (single canister), six respirator masks with filters and regulators as well as six replacement oxygen canisters (6 l steel / 6.8 l CFRP)
- Individual storage of the breathing apparatus in six transport boxes with hinged lid
- Division into three storage levels

- Storage of the six replacement oxygen canisters (steel / CFRP) in transport tubes PE tube ø 171 mm in a closed structure made of wooden platform boards
- Including storage tray made of aluminium with handle and transport boxes
- Further sizes and versions available on request
- Optionally also available with "Quadro" and "Quadro Light" undercarriage
- Scope of delivery without equipment items
- Series production quality equipment
- Stable and durable construction made of high-strength aluminium sections
- Platforms made of weatherproof wooden platform boards
- Ergo-Glow-Grip control unit – Continuous handlebar, oval-shaped for intuitive operation. Photoluminescent controls charge via UV radiation – for full functionality and safety even in the dark
- Robust and smooth-running actuating mechanism via flexible Bowden cable
- Two ball bearing castors Ø 200 mm with central wheel slewing arrestor for optimum handling
- Two ball bearing fixed castors Ø 200 mm with drum brake and dead man's function, resistant to dust, moisture and oil
- Foot-operated parking brake

Scope of supply

- Mobile container: 1 x

More product pictures



Added value

- The following equipment features are included as standard with every mobile container in the "Standard" assortment
- Body made of high-strength aluminium screw channel profile Connection of the profiles via stable, crossover corner screw connections – no welding!
- Markings for good visibility in the dark
- 2 fixed castors Ø 200 mm with internal drum brake and dead man's function
- 2 swivel castors Ø 200 mm with directional arrestors and central wheel and slewing arrestors
- Galvanised steel foot parking brake for swivel castors
- Operating control with ergonomic and continuous handle bars with SoftGrip coating
- Robust and smooth-running actuating mechanism via high-quality stainless steel Bowden cable

Corporate certifications

Standards for quality and sustainability

