MUNK
Sicherheit. Made in Germany.



Order no.: 115351

Telescopic ladder EU red DIN EN 1147

Length [mm]

3500 | 4400

Specification

Intended use Rescue	Ladder length 3.5 m	Ladder length retracted 800 mm	Ladder length extended 3.5 m	Setting angle 70 °
Clear width between rungs 270 mm	Outer width 500 mm	Ladder feet Ladder shoe	Depth of side-rails 100 mm	Width of side-rails 80 mm
Step/Rung height 28 mm	Step depth 29 mm	Number of steps/rungs 11 rungs	Max. load capacity 216 kg	Persons max. 2
Material Aluminium	Transport dimensions (plus packaging) 940 x 560 x 130 mm, 14.5 kg	Business division MUNK Rettungstechnik	Order no. 115351	

Facts

- Aluminium telescopic ladder
- Rescue ladder compliant with DIN EN 1147
- Abrasion-resistant anodised octagonal tube side-rails
- With heat-insulating, non-slip plastic coating

We reserve the right to make technical changes and price changes.

- Variable height adjustment via intuitive telescopic function (partial heights possible)
- Safety system for controlled retraction
- Minimises the risk of crushing and injury
- Permissible load: 250 kg / 2 people
- These products are covered by the statutory warranty

More product pictures



MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022