



Order no.: 120008

## Mobile container portable fire pump suction hoses vertical

Suction hoses

 upright

 horizontal

### Specification

Product type stehend	Length 1.2 m	Width 800 mm	Height 1.19 m	Height up to top edge of platform 621 mm
Max. load capacity 500 kg	Castor diameter 200 mm	Braking system Standard	Business division MUNK Rettungstechnik	Order no. 120008

### Facts

- Mobile container with "standard" undercarriage
- Folding operating unit for removing the suction hoses
- Suitable for holding the following equipment items:
  - 1x portable fire pump PFPN 10-1500
  - 4x suction hose A 1600 mounted vertically on the control unit
  - 1x standpipe BB (DN80 / 2B)
  - 1x underground hydrant wrench C
  - 1x surface hydrant wrench B
  - 3x coupling wrench ABC

- Drawer made of aluminium that can be pulled out on both sides (without brackets) for holding:
- 1x manifold A-BB
- 1x pressure hose B75 5 m
- 1x strainer basket A
- 1x wire protection cage A
- 2x multi-purpose line 20 m
- Fuel canister 10 l (low design)
- Further sizes and versions available on request
- Optionally also available with "Quadro" and "Quadro light" basic module
- Scope of delivery without equipment items
- Series production quality equipment
- Stable and durable construction made of high-strength aluminium sections
- Platforms made of weatherproof wooden platform boards
- Ergo-Glow-Grip control unit – Continuous handlebar, oval-shaped for intuitive operation. Photoluminescent controls charge via UV radiation – for full functionality and safety even in the dark
- Robust and smooth-running actuating mechanism via flexible Bowden cable
- Two ball bearing castors Ø 200 mm with central wheel slewing arrestor for optimum handling
- Two ball bearing fixed castors Ø 200 mm with drum brake and dead man's function, resistant to dust, moisture and oil
- Foot-operated parking brake

### Scope of supply

- Mobile container: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

- The following equipment features are included as standard with every mobile container in the "Standard" assortment
- Body made of high-strength aluminium screw channel profile Connection of the profiles via stable, crossover corner screw connections – no welding!
- Markings for good visibility in the dark
- 2 fixed castors Ø 200 mm with internal drum brake and dead man's function
- 2 swivel castors Ø 200 mm with directional arrestors and central wheel and slewing arrestors
- Galvanised steel foot parking brake for swivel castors
- Operating control with ergonomic and continuous handle bars with SoftGrip coating
- Robust and smooth-running actuating mechanism via high-quality stainless steel Bowden cable

## Corporate certifications

---

### Standards for quality and sustainability

