



Order no.: 063279

Wall anchor U-bracket, adjustable, 550–750 mm, galvanised steel

Wall clearance min [mm]

165 200 275 375 550 750

Specification

| Wall anchor | Wall distance min. | Wall distance max. | Adjustment range | Material |
|------------------------------------------------------|------------------------------------------------------|---------------------|------------------|------------------|
| U-bracket | 550 mm | 750 mm | 125 mm | Galvanised steel |
| Transport dimensions 670 x 530 x 70 mm, 8.5 kg | Business division MUNK Günzburger Steigtechnik | Order no. 063279 | | |

Facts

- Ideal for vertical ladders
- Very easy to install thanks to user-friendly design
- Adjustable wall anchor

Scope of supply

■ Wall anchor: 1 x

Information on sustainability criteria



Corporate certification: ISO 9001

■ Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning





Corporate certifications

Standards for quality and sustainability









