



Order no.: 033117

Wooden rung single ladder nivello® traverse



Number of rungs

12

14

Specification

Working height 4.7 m	Step design Sprossen	Number of steps/rungs 12 rungs	Step/Rung height 40 mm	Step depth 21 mm
Step/Rung distance 280 mm	Ladder length 3.6 m	Outer width 420 mm	Stabiliser width 930 mm	Depth of side-rails 70 mm
Width of side-rails 27 mm	Max. load capacity 150 kg	Design type Zum Anlehnen	Transport dimensions (plus packaging) 3565 x 420 x 70 mm, 12.9 kg	Business division MUNK Günzburger Steigtechnik
Order no. 033117				

Facts

- Rung straight ladder made of wood
- Side-rails made of finger-jointed pine or knot-free Caroline pine, rungs made of ash
- Pegged rung-to-side-rail connection, resulting in smooth side-rail surface
- Rung distance: 280 mm

- Ladder width: 420 mm (without stabiliser)
- Wooden stabiliser with non-slip ladder shoes with optimum width for the selected product. Ensures maximum stability and safe ascent for straight ladders over 3.0 m. The stabiliser is enclosed separately and is screwed to the lower end of the rail in two places
- Maximum load: 150 kg

Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x

More product pictures



Added value

Industrial grade

- Sturdy processing for demanding applications (e.g. 4-fold edging)
- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories

Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



Corporate certifications

Standards for quality and sustainability

