



Order no.: 035322

## Rung single ladder GRP/aluminium with nivello® crossbar



Number of rungs

12

14

### Specification

Working height 4.7 m	Step design Rungs	Number of steps/rungs 12 rungs	Step/Rung height 30 mm	Step depth 30 mm
Step/Rung distance 280 mm	Ladder length 3.58 m	Outer width 420 mm	Stabiliser width 930 mm	Depth of side-rails 58 mm
Width of side-rails 25 mm	Max. load capacity 150 kg	Design type To lean against	Transport dimensions (plus packaging) 3547 x 427 x 85 mm, 9.5 kg	Predecessor product 035312
Business division MUNK Günzburger Steigtechnik	Order no. 035322			

### Facts

- Rung straight ladder made of reinforced fibre glass/aluminium
- Side-rails made of reinforced fibre glass profiles
- Rectangular rungs grooved on both sides 30 x 30 mm, aluminium
- 4-fold edged rung-to-side-rail connection

- Rung distance: 280 mm
- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg
- Suitable for working near or on live parts
- Tested up to 1,000 volts in accordance with DIN EN 61478:2002 Section 6.5.1 and A1:2004 Category 1
- Stabiliser made of reinforced fibre glass with non-slip ladder shoes in optimal width for the selected product
- Note: Products with GFRP content are non-returnable, due to their sensitivity; the statutory warranty applies (ageing resistance 10 years)

### Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality

- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures



Added value


### roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



### Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



### Fiberglass

Ladders made of GFRP offer the perfect properties for special challenges. [Find out](#) what makes GFRP such a special material, how we use it for ladders and where these ladders are used.



## Corporate certifications

### Standards for quality and sustainability



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID: 9108612548



**Nachhaltigkeit**  
**EcoVadis**  
sustainable supply management  
CSR-Rating in Silber 2022

