



Order no.: 036822

GRP rung single ladder with nivello® traverse



Number of rungs

12

14

Specification

Working height 4.7 m	Step design Rungs	Number of steps/rungs 12 rungs	Step/Rung height 29 mm	Step depth 28 mm
Step/Rung distance 280 mm	Ladder length 3.59 m	Outer width 420 mm	Stabiliser width 930 mm	Depth of side-rails 73 mm
Width of side-rails 25 mm	Max. load capacity 150 kg	Design type To lean against	Transport dimensions (plus packaging) 3560 x 430 x 90 mm, 11.94 kg	Business division MUNK Günzburger Steigtechnik
Order no. 036822				

Facts

- Rung straight ladder made of reinforced fibre glass
- Side-rails and rungs made of reinforced fibre glass plastic profiles
- Rectangular rungs grooved on both sides, 28 x 29 mm

- By using the metal suspension step, the insulation voltage is reduced to 1,000 V
- High-strength rung-to-side-rail connection
- Rung distance: 280 mm
- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg
- Tested in accordance with DIN EN 61478:2002 + DIN EN 61478/A1:2004, Section 6.5.1, Category 1: 28,000 V
- Stabiliser made of reinforced fibre glass with non-slip ladder shoes in optimal width for the selected product
- Note: Products with GFRP content are non-returnable, due to their sensitivity; the statutory warranty applies (ageing resistance 10 years)

Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany

- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



Corporate certifications

Standards for quality and sustainability



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID: 9108612548



Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022

