



Order no.: 036628

2-section GRP rung extension ladder with nivello® traverse



Number of rungs

2x10 2x12

Specification

Working height 5.2 m	Step design	Number of steps/rungs	Step/Rung height	Step depth
	Rungs	2x 8 rungs	29 mm	28 mm
Step/Rung distance	Retracted length	Extended length	Outer width	Stabiliser width
280 mm	2.5 m	4.18 m	420 mm	930 mm
Depth of side-rails 73 mm	Width of side-rails 25 mm	Design type To lean against 2- part	Transport dimensions 2440 x 430 x 144 mm, 15.5 kg	Business division MUNK Günzburger Steigtechnik
Order no. 036628				

Facts

- Rung push-up extension ladder made of glassfibre reinforced plastic
- Side-rails made of reinforced fibre glass rectangular tube profiles
- Rectangular rungs grooved on both sides, 28 x 29 mm



- By using the metal suspension step, the insulation voltage is reduced to 1,000 V
- High-strength rung-to-side-rail connection
- Galvanised steel fittings
- Easy height adjustment from rung to rung
- Upper ladder from size 2 x 12 with wall wheels
- Corrosion-resistant guide fixtures
- Upper ladders up to 3.0 m with nivello® ladder shoes
- Rung distance: 280 mm
- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg
- Standard stabiliser with non-slip ladder shoes with optimum width for the selected product. Ensures maximum stability and safe ascent for straight ladders over 3.0 m. The stabiliser is enclosed separately and is screwed to the lower end of the rail in two places
- Suitable for working near or on live parts
- Tested in accordance with DIN EN 61478:2002 + DIN EN 61478/A1:2004, Section 6.5.1, Category 1: 28,000 V
- Note: In accordance with standards, the attached push-up extension ladder section cannot be separated from the ladder with lengths over 3.0 m
- Note: Products with GFRP content are nonreturnable, due to their sensitivity; the statutory warranty applies (ageing resistance 10 years)

Scope of supply

Ladder: 1 x

Stabiliser (enclosed separately): 1 x

Information on sustainability criteria

Corporate certification: ISO 9001



Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Added value

Optimum and smooth operation, thanks to easily accessible elements

- Simple height adjustment from rung to rung or from step to step
- Wall wheels on the upper part (from 14 rungs or more)
- Fittings with sliding guides
- Smooth-running rope pulley



Fiberglass

Ladders made of GFRP offer the perfect properties for special challenges. <u>Find out</u> what makes GFRP such a special material, how we use it for ladders and where these ladders are used.



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders





Corporate certifications

Standards for quality and sustainability









