



Order no.: 115544

Folding scaffolding with triple platform

Platform height [mm]

2510

4470

6430 8390

Specification

Working height 6.47 m	Scaffolding length 2.61 m	Scaffolding width 2.17 m	Scaffolding height 5.74 m	Platform width 1.9 m
Platform length 2.45 m	Load capacity 1.5 kN/m2	Transport dimensions 2850 x 1900 x 950 mm, 299 kg	Indoor use, central installation possible & allowed	Outdoor use, central installation possible & allowed
Ballasting of scaffolding, indoor, central installation 0 kg	Ballasting of scaffolding, outdoor, central installation 130 kg	Business division MUNK Günzburger Steigtechnik	Notice Accessories necessary to fulfil DIN EN 1004-1:2021	Platform height 4.47 m

Facts

- Mobile scaffolding made of sturdy round aluminium tubing with welded frame parts
- Double folding frame made of rectangular tube side-rails with self-locking hinges
- Large work area of 4.5 m²
- Space-saving transport and storage
- Four Ø 200 mm swivel castors with centric load application, locking mechanisms and spindles
- Aluminium toe boards and railing frames with integrated knee board as safety railing



- Simple setup and removal without tools
- GS-tested as per DIN EN 1004
- Load class/scaffolding group 2: 1.5 kN/m²
- In order to meet the requirements of DIN EN 1004-1:2021, this scaffold must be retrofitted
- Option 1 Conversion to MSG: 2 protective assembly railings telescopic (027991) are required for safe assembly, dismantling and conversion
- Option 2 Conversion to SG: Replace the railings lengthwise with safety railings for mobile scaffoldings in the appropriate scaffold length (2 pieces per platform level). Replace the guardrail frame at the front (top platform level) with railing frame SG at the front in the appropriate width. Omit the diagonal braces above the first platform

Scope of supply

■ Folding frame unit, 1.9 m: 1 x

■ Push-fit frame 190: 2 x

Platform without flap: 4 x

Platform with trapdoor: 2 x

Push-fit frame 190/112: 2 x

Railing lengthwise: 4 x

Diagonal brace: 8 x

Step-on bracket: 1 x

Toe board front side: 2 x

■ Toe board long side: 2 x

Swivel castor with spindle: 4 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

RoHS

■ REACH

The MUNK Group complies with a Code of Conduct

The Supply Chain Act does not apply due to our size



- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard,
 small amounts of plastic
- No health hazards for the users

More product pictures





Added value

Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools



Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application



Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant





Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs



Expand your scaffolding with a safety railing (SG) and ensure reliable protection at work thanks to the system-integrated side protection! The retrofit reduces the risk of falling and enables the BG BAU work safety subsidy to be paid for up to 50% of the purchase costs (max. 100 euro per measure).

✓ Suitable for this product: Compatible SG safety railings offer effective side protection and are easy to retrofit.

All members of the BG BAU profit from this subsidy. This is intended to prevent accidents at work and improve ergonomics, especially on construction sites. All information from BG BAU can be found at: www.bgbau.de/service/angebote/arbeitsschutzpraemie

A brief overview of the subsidy and an overview of our eligible products can be found on our website at <u>Knowledge</u>.



Corporate certifications

Standards for quality and sustainability









