MUNK
Sicherheit. Made in Germany.



Order no.: 115463

Step telescopic ladder Prime Line

Number of steps

9 | 13

Specification

Working height max. 3.8 m	Number of steps/rungs 9 steps	Step depth 80 mm	Step/Rung distance 300 mm	Step design Steps
Retracted length 760 mm	Extended length 3 m	Inclination 75 °	Outer width 470 mm	Max. load capacity 150 kg
Design type To lean against	Transport dimensions (plus packaging) 810 x 470 x 105 mm, 11.44 kg	Predecessor product 115473	Business division MUNK Günzburger Steigtechnik	Order no. 115463

Facts

- Original Telesteps telescopic ladder made of aluminium
- Sturdy triangular side-rails, anodised for abrasion resistance
- 80 mm deep, ribbed steps and three rungs (50 mm)
- High-strength step-to-side-rail connection
- Convenient height adjustment through intuitive telescopic function

- For ladder length 4.10 m including folding stabiliser (enclosed separately)
- Step spacing: 300 mm
- Maximum load: 150 kg
- These products are covered by the statutory warranty

Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x

More product pictures







Added value

Easy handling

- Centrally mounted, automatically locking steel hinges for quick change of functions
- With Telesteps: Sturdy joints on folding units guarantee durability



Ratchet handles

- Easy to handle thanks to ergonomic shape
- Stable and safe thanks to steel core and aluminium cover



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



practical and compact

- Thanks to the telescopic function, the ladders can be folded/moved together to take up minimum space when not in use
- Space-saving storage and easy transport

Flexible use

- Various application options
- Can be used as a height-adjustable step and straight ladder



Height adjustment

- The height-adjustable ladder sections are ideal for use on stairs
- Intuitive telescoping of the ladder through clearly visible levers or ratchet handles



Safe standing

- Stabilisers in optimum widths for the ladder model
- Conical construction (without stabiliser) or bevelled rubber shoes



Certificates



Z1 070102 0012
Rev. 00 - Certificate

Valid in

DIN EN 131-6:2019
DIN EN 131-3:2018
DIN EN 131-1:2015/A1:2019

Corporate certifications

Standards for quality and sustainability

