



Order no.: 036325

Platform ladder made of
GRP / aluminium, folding
and mobile, with GRP
handrail



Number of steps

5

6

7

8

Specification

Working height 3.15 m	Step design Stufen	Number of steps/rungs 5 steps	Platform included as step Ja	Platform height 1.17 m
Platform length 650 mm	Platform width 600 mm	Step depth 80 mm	Step/Rung distance 235 mm	Height 2.17 m
Base spread 1.4 m	Inclination 70 °	Outer width 650 mm	Stabiliser width 1 m	Depth of side-rails 73 mm
Depth of side-rails, support 58 mm	Castor diameter 125 mm	Max. load capacity 150 kg	Design type Freistehend Einseitig begehbar Mit Fahrbalken	Transport dimensions (plus packaging) 2710 x 750 x 220 mm, 33 kg
Predecessor product 036305	Business division MUNK Günzburger Steigtechnik	Order no. 036325		

Facts

- Platform ladder made of reinforced fibre glass/aluminium
- Side-rails made of reinforced fibre glass rectangular tube profiles

- Grooved steps with a depth of 80 mm, made of aluminium
- 4-fold edged step-to-side-rail connection
- Spacious platform made of reinforced fibre glass grating (650 x 600 mm)
- Handrail on both sides for safe ascending and descending
- All-round railing on three sides (height 1000 mm) including knee rail and toe board as well as safety rope for maximum fall protection
- nivello® ladder shoes with patented 2-axis inclination technology
- Support part with narrow stabiliser bar and Ø 125 mm fixed castors with locking device for quickly moving to a new location when folded out
- Folds for compact storage thanks to sturdy steel hinges
- Generous sized tool tray
- Step spacing: 235 mm
- Tested up to 1,000 volts in accordance with DIN EN 61478:2002 Section 6.5.1 and A1:2004 Category 1
- Ladder inclination: 70°
- Maximum load: 150 kg
- Delivery time: 15 days
- Suitable for working near or on live parts
- Note: Products with glass-fibre reinforced plastic content are non-returnable due to their sensitivity

Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Safe working

- Handrails for safe ascent and descent
- Large-format, non-slip platforms
- Conical side-rail guide for safe stance
- Railings and knee boards for safe access and stance



The movable ladder shoe sets new standards in stability

[Learn more](#)



Fiberglass

Ladders made of GFRP offer the perfect properties for special challenges. [Find out](#) what makes GFRP such a special material, how we use it for ladders and where these ladders are used.



Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Castors

- Ergonomic and comfortable handling
- Simple movement from place to place



Corporate certifications

Standards for quality and sustainability

