MUNK
Sicherheit. Made in Germany.



Order no.: 632306

Stair module grooved aluminium

Number of steps

6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15

Specification

Inclination 45 °	Number of steps/rungs 6 steps	Step width 800 mm	Step depth 225 mm	Design type 45°
Surface Aluminium corrugated	Base area 1.8 m	Predecessor product 332306	Business division MUNK Günzburger Steigtechnik	Order no. 632306

Facts

- A stair module consists of stairs with a handrail on both sides, a platform, a railing on the front and a safety door
- Standard step and platform design in grooved aluminium (R 9), optionally also in steel grating (R 12), aluminium grating (R 13), perforated steel cover (R 13) or perforated aluminium cover (R 13)
- Inclination: 45°
- Step width: 800 mm
- Step depth: 225 mm
- Rigid handrails and railings with toe and knee boards on both sides (height: 1,100 mm)

We reserve the right to make technical changes and price changes.

- Stationary attachment by means of foot bracket
- Maximum load: 1.5 kN/m2, step load 150 kg, total load 300 kg
- Note: When ordering, please specify the exact height (platform height) required at the factory. The stair modules are delivered custom-fit in accordance with your requirements. Intermediate dimensions are supplied at the price of the next higher number of steps, other stair inclinations on request
- Production in compliance with European standards DIN EN ISO 14122 and DIN EN 1004
- This product is made to order and cannot be returned

Scope of supply

- Stair module: 1 x
- Instructions for use and operation: 1 x

More product pictures



Added value

Product configurator

Configuring, enquiring about and ordering individual products could not be easier with our product configurator for stairs, bridging steps and mobile platform stairs. Simply enter your required dimensions and versions step by step, and a rotating 3D model will appear in real time. To save your configuration and request a quotation requires a login which will be set up for you by our Sales team.




Modular kit system

- Individually and cost-efficiently combinable for the respective requirement
- Platform heights from 1.25 to 3.0 m
- Three different platform lengths can be selected

Safety railing

- Railings and handrails on both sides ensure a high level of safety at work
- Fixed size or telescopic safety door



Ascent

- Non-slip designs for secure footing
- All kinds of different materials can be selected with non-slip classes from R 9 to R 13 – suitable for the specific application purpose



Modular walkway systems

- For a wide range of indoor applications in production, warehouses, as access to machines, as a walkway along building walls or as practical access for de-icing commercial vehicles in the winter months
- Thanks to innovative modular construction, walkway systems can be assembled conveniently, cost-effectively and yet precisely to meet individual requirements
- The platform height of the walkway systems can be individually determined between 1.25 and 3.0 metres. The desired total length is achieved by way of combining three different walkway lengths
- The modules can be easily assembled using pre-assembled modules, securely connected to one another and fastened to the underlying surface using foot brackets
- The maintenance-free modules are manufactured as a stable, corrosion-resistant aluminium construction with a supporting frame.
- Maximum load: 1.5 kN / m², step load 150 kg, total load 300 kg
- Access to the walkway conveniently via stairs 45° with handrails on both sides and automatically closing safety door.
- The delivery from the factory is made in pre-assembled modules for quick and simple assembly in accordance with the enclosed assembly instructions

Note

When assembling a walkway, only modules with the same platform height can be combined. Please contact us if you need different platform heights on a walkway system. This also applies if you need walkway systems for outdoor use, as they are primarily designed for indoor use (with the exception of de-icing systems).

Corporate certifications

Standards for quality and sustainability

