

Order no.: 012042

## Pit ladder lower section



Number of steps

2

4

## Specification

Depth of excavation min. 1.3 m	Depth of excavation max. 1.6 m	Ladder length 800 mm	Number of steps/rungs 2 steps	Lower outer width 420 mm
Depth of side-rails 73 mm	Width of side-rails 25 mm	Step width 370 mm	Step depth 80 mm	Step/Rung distance 263 mm
Inclination 70 °	Max. load capacity 150 kg	Type of non-slip protection clip-step R13	Design type Zum Anlehnen	Material Aluminium
Transport dimensions (plus packaging) 804 x 507 x 87 mm, 2.8 kg	Business division MUNK Günzburger Steigtechnik	Order no. 012042		

## Facts

- Aluminium ladder push-fit section
- Two different push-fit sections for flexible extension of the pit ladder
- 80 mm-deep steps with clip-step R13 slip-resistant step padding
- Easy and fast installation, thanks to push-fit connections with hook lock

- Tool-free conversion of pit ladder base plates with claws on push-fit section
- Lightweight individual components
- Space-saving transport and storage

### Scope of supply

- Push-fit section: 1 x
- Assembly instructions and instructions for use: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures



## Added value

### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)


- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



### clip-step R 13 step padding

Certified non-slip protection for step ladders

- Fulfils the requirements of the highest possible non-slip class R 13 thanks to aluminium oxide particles
- Improves work safety in wet and oil-contaminated environments
- Applied up to the maximum accessible step as a visual check
- Retrofittable, available as a spare part and also in yellow in selected lengths (RAL 1021)



### Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



### Sponsored by BG BAU

Specification subject to conditions; for the latest information please visit the BG BAU website (statutory accident insurance company for the construction and construction related services in Germany). Since 2014, the BG BAU has been promoting the purchase of platform ladders, step stools and ladder accessories with single-sided and double-sided access. All members of the BG BAU profit from this. This aims to prevent work accidents on building sites and improve ergonomic working practices. For more information by BG BAU, please visit:

[www.bgbau.de/service/angebote/arbeitsschutzpraemie](http://www.bgbau.de/service/angebote/arbeitsschutzpraemie)

A brief overview of the subsidy and an overview of our eligible products can be found on our website under [know-how](#).

## Corporate certifications

---

### Standards for quality and sustainability



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

