



Order no.: 114067

3-section rope-extension ladder DIN EN 1147

Number of rungs

3x10

3x11

3x12

3x13

3x14

3x15

3x16

3x17

Specification

Intended use Rettung	Ladder length retracted 3.5 m	Ladder length extended 7.7 m	Setting angle 70 °	Clear width between rungs 270 mm
Clear width, upper ladder 350 mm	Clear width, central ladder 420 mm	Clear width, lower ladder 420 mm	Outer width 490 mm	Ladder feet Stahlspitze
Depth of side-rails 74	Step/Rung height 28 mm	Step depth 29 mm	Number of steps/rungs 3x 10 rungs	Max. load capacity 324 kg
Persons max. 3	Material Aluminium	Rung covering Standard (rot)	Business division MUNK Rettungstechnik	Order no. 114067

Facts

- 3-section rope-extension ladder made of aluminium
- Rescue ladder compliant with DIN EN 1147
- With rope pulley, locking hook and rope brake
- With heat-insulating, non-slip plastic coating
- 4-fold edged rung-to-side-rail connection

- Corrosion-resistant fixtures made of galvanised steel
- Lower ladder with steel spikes at the base
- Upper ladder with wall wheels
- Permissible load: 324 kg / 3 people

More product pictures



Corporate certifications

Standards for quality and sustainability

