MUNK
Sicherheit. Made in Germany.



Order no.: 077435

Sprouted double-barred mast ladder

type

Plug-in part 1 | Plug-in part 2 | Lower part

Specification

Ladder length 1.95 m	Number of steps/rungs 7 rungs	Outer width 645 mm	Depth of side-rails 58 mm	Max. load capacity 150 kg
Business division MUNK Günzburger Steigtechnik	Order no. 077435	Length 2.05 m	Weight 16.8 kg	

Facts

- Aluminium rung ladder
- Base section with ground spikes and two attachment points on the mast
- Modular ladder design with plug-in sections to suit the required length
- Innovative clamping mechanism with a rope around the mast
- Sturdy rectangular tubular struts and plug-in connections at the ladder head
- Integrated stainless steel anti-slip rail for PPE
- Rectangular rungs grooved on both sides, 30 x 30 mm, Slip resistance class R10

We reserve the right to make technical changes and price changes.

- 4-fold edged rung-to-side-rail connection
- Rung distance: 280 mm
- Ladder width: 470 mm
- Maximum load: 150 kg

Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x

More product pictures







Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022