

Order no.: 127112

ML FlexxLift



Specification

Working height 4 m	Platform height max. 2 m	Cage length 740 mm	Cage width 610 mm	Base area length 750 mm
Base area width 610 mm	Height 2 m	Inclination 0 °	Max. load capacity 135 kg	Transport dimensions 1180 x 735 x 1670 mm, 275 kg
Business division MUNK Günzburger Steigtechnik	Order no. 127112			

Facts

- Manually operated vertical mast lift with intuitive one-handed operation
- All-round secured working area up to working heights of 4.00 m indoors
- low weight for easy handling
- Automatic braking device when lifting the workman basket
- Stepless and non-electric lifting mechanism with gas pressure spring



- Easy to enter and exit via swing door
- Robust design for extra durability
- Low operating costs, practically maintenancefree
- Anti-theft device with padlock
- These products are covered by the statutory warranty

Scope of supply

Lift: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users



More product pictures











Corporate certifications

on sustainability criteria







