



Order no.: 115513

**Tactical Line telescopic
ladder, black, 3.5 m, DIN
EN 1147**

Design

3,5

4,1

Specification

Rescue height 4300	Intended use Rettung	Ladder length 3.5 m	Ladder length retracted 1.12 m	Setting angle 70 °
Outer width 470 mm	Depth of side-rails 100 mm	Width of side-rails 75 mm	Number of steps/rungs 11 rungs	Max. load capacity 500 kg
Persons max. 3	Material Aluminium	Rung covering schwarz	Transport dimensions (plus packaging) 1120 x 490 x 125 mm, 15.6 kg	Business division MUNK Rettungstechnik
Order no. 115513				

Facts

- Aluminium telescopic ladder
- Rescue ladder compliant with DIN EN 1147
- Abrasion-resistant anodised triangular tube side-rails (partly plastic-coated)
- With heat-insulating, non-slip plastic coating

- Variable height adjustment via intuitive telescopic function (partial heights possible)
- Safety system for controlled retraction
- Minimises the risk of crushing and injury
- These products are covered by the statutory warranty

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

Standards for quality and sustainability

