

Order no.: 127129  
**FlexxLift 5.0 MD**



Specification

|                             |                           |                                                                             |                                   |                              |
|-----------------------------|---------------------------|-----------------------------------------------------------------------------|-----------------------------------|------------------------------|
| Working height<br>5 m       | Platform length<br>890 mm | Platform width<br>645 mm                                                    | Approved for outdoor<br>use<br>No | Max. load capacity<br>180 kg |
| Platform height max.<br>3 m | Inclination<br>0 °        | Transport dimensions<br>(plus packaging)<br>1230 x 770 x 1765<br>mm, 380 kg | Order no.<br>127129               |                              |

Facts

- Self-propelled vertical mast lift, working height 5.00 m
- Maximum load capacity: 180 kg (person plus equipment)
- Battery-powered drive and lifting system – self-propelled and emission-free
- Operated via a central joystick – suitable for both right- and left-handed users
- 24 V battery technology with integrated charger, operating hours counter and charge level indicator
- Travel speed up to 4 km/h, reduced depending on altitude

Description

If you're constantly changing position, you waste time moving the platform around. The FlexxLift 5.0 MD self-propelled vertical mast platform lifts and moves you to a working height of 5.00 m via a joystick – smoothly and quietly. You control it, rather than pushing it.

Self-propulsion and lifting via joystick

Both travel and lifting are battery-powered and emission-free – you operate both via the central joystick, which is equally comfortable for right- and left-handers. Instead of pushing the platform to the next location, you drive there and raise yourself to

- Open work basket with horizontal knee rail
- Tested in accordance with EN 280 (Class 1A), CE conformity and test report

the required height. At speeds of up to 4 km/h, reduced depending on height for safety.

Battery charge level and operating hours at a glance

You can charge the maintenance-free 24 V system via the integrated charger – no external device is required. The operating hours counter and charge level indicator keep you informed at all times. If the battery runs flat, the emergency lowering function and decouplable drive system keep the platform mobile, so you can still move it out of the way.

Open basket – loaded from the side, without having to reach over

In the open basket, you can load and unload your materials conveniently from the side, rather than having to lift them over a high edge. This means you can reach items in the lower section effortlessly too.

Low unladen weight

Weighing just 380 kg, the platform remains light enough to protect sensitive floors.

Tested safety – with certification

The stage has been tested in accordance with EN 280 (Class 3A); the CE Declaration of Conformity and test report are available in German. A 12-month warranty applies.

Request your quote now.

## Scope of supply

- Lift: x
- Instructions for use and operation: x

## More product pictures



Corporate certifications

Standards for quality and sustainability

