



Order no.: 127130

FlexxLift 5.0 SP

Specification

Platform length 1.11 m	Platform width 765 mm	Base area length 1.11 m	Base area width 631 mm	Approved for outdoor use No
Max. load capacity 240 kg	Transport dimensions (plus packaging) 1273 x 765 x 1776 mm, 390 kg	Business division MUNK Günzburger Steigtechnik	Order no. 127130	

Facts

- Vertical scissor lift, working height 5.00 m
- Max. load capacity 240 kg – large platform (1.11 x 0.63 m)
- Electric lift – manually operated (push) system. Particularly manoeuvrable and easy to handle
- Operated via a central joystick – suitable for both right- and left-handed users
- 24 V battery technology with integrated charger, operating hours counter and charge level indicator
- Open work basket with horizontal knee rail

Description

If you need space and load capacity at height, a ladder is not the right choice. The FlexxLift 5.0 SP vertical scissor lift can carry 240 kg on a large platform up to a working height of 5.00 m. It is electrically powered and manoeuvred by hand.

Plenty of space, high load capacity

The platform measures 1.11 x 0.63 m – enough space for one person plus tools and materials. The hydraulic scissor mechanism lifts quickly and safely and supports up to 240 kg. You can work at height without having to compromise on tools or payload.

- Transport width 631 mm, net weight 390 kg – fits through standard doorways, suitable for vans and lifts
- Forklift pockets and lifting eyes
- Tested in accordance with EN 280 (Class 1A), CE conformity and test report

Maximum stability thanks to the scissor mechanism

The scissor mechanism guides the platform vertically and evenly during lifting – giving the platform a steady, firm footing at the top. This means you remain stable at full working height and can concentrate on the task at hand rather than on the platform.

Electric lifting, manoeuvrable movement – excellent value for money

Lifting is controlled electrically via the central joystick, which is equally comfortable for both right- and left-handed users. To move the platform, you simply push it yourself. This combination of electric lifting and manual movement makes the SP particularly manoeuvrable in confined spaces and offers excellent value for money, as you get the convenience of electric lifting without the need for an expensive drive system.

Battery charge level and operating hours at a glance

The maintenance-free 24 V system is charged via the integrated charger. The operating hours counter and charge level indicator keep you informed at all times.

Open platform – loaded from the side, without having to reach over the edge

With the open platform, you can load and unload your materials conveniently from the side, rather than having to lift them over a high edge. This means you can reach items at the bottom with ease.

Easy to transport – through doors, into vans and lifts

With a transport width of 631 mm, you can wheel the platform through standard doors and into

standard vans. Use the forklift pockets and crane eyes for transport. Check the platform's net weight of 390 kg against your lift's load capacity beforehand.

Tested safety – with certification

The platform is tested in accordance with EN 280 (Class 3A); you will receive the CE Declaration of Conformity and test report in German. A 12-month warranty applies. Request your quote now.

Scope of supply

- Lift: x
- Instructions for use and operation: x

More product pictures



Corporate certifications

Standards for quality and sustainability

