

Order no.: 930209

Mounting bracket 30x30 mm



Type

30x30

40x40

Specification

Material Stahl verzinkt	Profile dimension X 30 mm	Profile dimension Y 30 mm	Weight/piece 46 g	Groove size 6 mm
Dimension A 27 mm	Dimension B 34 mm	Dimension C 4 mm	Business division MUNK Profiltechnik	Order no. 930209

Facts

- Profile angle for profile 30
- Flat, space-saving angle
- For joining profiles to each other
- For assembling different components
- No machining required

Description

Flat mounting bracket for space-saving profile connections! The MUNK mounting bracket made of galvanised steel creates stable 90° connections – without machining and with minimal space requirements.

Space-saving & robust design

- Flat design: Only 4 mm (30×30) or 5 mm (40×40) material thickness for minimal space requirements between profiles
- Galvanised steel: corrosion protection for continuous use in industrial and outdoor applications

- Weight-optimised: 46 g (30×30) or 100 g (40×40) – lighter than die-cast corner brackets

Universally applicable without machining

Suitable for all MUNK construction profiles with 6 mm T-slots (30 mm profiles) or 8 mm T-slots (40 mm profiles). No machining required – insert the slot nuts, attach the angle bracket, screw it in place.

Versatile connection options

- Profile connections: Stable frame corners for machine frames and enclosures
- Component assembly: Fastening of panels, sheets or accessories
- Bracing: Retrofitting of existing constructions

Typical areas of application

- Machine frames: Space-saving corner connections in confined spaces
- Protective & test enclosures: Flat assembly without annoying protrusions
Assembly tables: Fastening of worktops or side components
- Transport frames: Lightweight bracing for mobile constructions

Discover the MUNK mounting bracket – the slim alternative for profile connections that saves space today and can be flexibly expanded tomorrow.

Scope of supply

- Mounting bracket: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001

- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

Standards for quality and sustainability

