



Order no.: 033812

Double-sided stepladder wood



Number of steps/rungs

2x5

2×3
270

2x4



2x7

2x8

Specification

Working height 3.1 m	Step design Steps + Rungs mixed	Number of steps/rungs 2x 6 steps	Step/Rung height 20 mm	Step depth 80 mm
Step/Rung distance	Ladder length	Total length folded	Base spread	Inclination 70 °
250 mm	1.8 m	1.8 m	1.27 m	
Lower outer width	Upper outer width 430 mm	Depth of side-rails	Width of side-rails	Max. load capacity
555 mm		65 mm	22 mm	150 kg
Design type Freestanding Double-sided access	Transport dimensions 1800 x 560 x 145 mm, 11 kg	Business division MUNK Günzburger Steigtechnik	Order no. 033812	

Facts

- Double-sided stepladder made of wood
- Solid softwood timber side-rails, beech steps
- Grooved steps with a depth of 80 mm
- Die obersten beiden Sprossen aus Buche 22 x 44 mm



- Pegged step-to-side-rail connection, resulting in smooth side-rail surface
- Sturdy steel hinges
- Supplied as standard with practical bucket hook
- Spread protection through firmly screwed textile straps
- plastic transport lock at the base of the ladder

Step spacing: 230 mm

Ladder inclination: 70°

Maximum load: 150 kg

These products are covered by the statutory warranty

Scope of supply

Ladder: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality



- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Added value

Industrial grade

- Sturdy processing for demanding applications (e.g. 4-fold edging)
- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories

Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on <u>TRBS 2121 Part 2</u> has been summarised on our Service page
- Read our <u>tips and tricks</u> on how to calculate working <u>height</u>





Corporate certifications

Standards for quality and sustainability









