


Order no.: 115545

Folding scaffolding SG with triple platform



Platform height [mm]

2510 4470 6430 8390

Specification

Working height 6.47 m	Scaffolding length 2.61 m	Scaffolding width 2.17 m	Scaffolding height 5.74 m	Platform width 1.9 m
Platform length 2.45 m	Load capacity 1.5 kN/m ²	Transport dimensions (plus packaging) 3000 x 2000 x 1100 mm, 304 kg	Indoor use, central installation possible & allowed	Outdoor use, central installation possible & allowed
Ballasting of scaffolding, indoor, central installation 0 kg	Ballasting of scaffolding, outdoor, central installation 130 kg	Business division MUNK Günzburger Steigtechnik	Platform height 4.47 m	

Facts


- Mobile scaffolding made of sturdy round aluminium tubing with welded frame parts
- Secured all around thanks to leading railing, can be assembled and dismantled from level to level
- Double folding frame made of rectangular tube side-rails with self-locking hinges
- Large work area of 4.5 m²
- Space-saving transport and storage

- Four swivel castors, Ø 200 mm, with central load distribution, brakes and spindles for height adjustment
- Aluminium toe boards and railing frames with integrated knee board as safety railing
- Simple setup and removal without tools
- Load class/scaffolding group 2: 1.5 kN/m²
- Additional side boards for intermediate platforms are available as an option for country-specific requirements (e.g. Austria and France)

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools




Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application



Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant



Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs



This product can be funded as part of the BG BAU work safety subsidies! Subsidy subject to conditions; for the latest information, please visit the homepage of BG BAU.

Our safety railing (SG) is a system-integrated side protection that minimises the risk of falling during assembly, conversion and dismantling, as well as when using working and protective scaffolding. With this technical protection you meet the highest safety standards and at the same time benefit from an attractive subsidy of up to 50% of the purchase costs (max. 100 euro per measure).

✓ For new mobile scaffolding: The safety railings are eligible as part of a complete working platform (including safety railings and frame parts).

✓ For existing scaffolding: Retrofits with compatible safety railings are possible.

All members of the BG BAU profit from this subsidy. This is intended to prevent accidents at work and improve ergonomics, especially on construction sites. All information from BG BAU can be found at: www.bgbau.de/service/angebote/arbeitsschutzpraemie

A brief overview of the subsidy and an overview of our eligible products can be found on our website at [Knowledge](#).

Corporate certifications

Standards for quality and sustainability



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

