



Order no.: 011169

Rung straight ladder 350 mm wide without stabiliser



Number of rungs

6	7	8	9	10	12	14	16	18
20	22	24						

Specification

Working height 5.9 m	Step design Rungs	Number of steps/rungs 18 rungs	Step/Rung height 30 mm	Step depth 30 mm
Step/Rung distance 280 mm	Type of non-slip protection Aluminium corrugated	Ladder length 5.28 m	Inclination 70 °	Outer width 350 mm
Depth of side-rails 73 mm	Width of side-rails 24.5 mm	Max. load capacity 150 kg	Design type To lean against	Transport dimensions (plus packaging) 5280 x 355 x 83 mm, 12 kg
Business division MUNK Günzburger Steigtechnik	Order no. 011169			

Facts

- Aluminium rung straight ladder
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Rung distance: 280 mm

- Ladder width: 350 mm
- nivello® ladder shoes with patented 2-axis inclination technology
- Maximum load: 150 kg
- Note: Straight ladders over 3.0 m can be used without a stabiliser only when they are used exclusively for their intended purpose (e.g. permanently installed, fitted with hooks, fastened with a belt)

Scope of supply

- Ladder: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

Added value

The movable ladder shoe sets new standards in stability

[Learn more](#)



Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



Corporate certifications

Standards for quality and sustainability



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

