



Order no.: 010016

# Rung straight ladder without stabiliser



Number of rungs

- 6
- 8
- 10
- 12
- 14
- 16
- 18
- 20
- 24

## Specification

|                              |                                                           |                                   |                                                                         |                                                      |
|------------------------------|-----------------------------------------------------------|-----------------------------------|-------------------------------------------------------------------------|------------------------------------------------------|
| Working height<br>5.8 m      | Step design<br>Rungs                                      | Number of steps/rungs<br>16 rungs | Step/Rung height<br>30 mm                                               | Step depth<br>30 mm                                  |
| Step/Rung distance<br>280 mm | Type of non-slip<br>protection<br>Aluminium<br>corrugated | Ladder length<br>4.72 m           | Outer width<br>420 mm                                                   | Depth of side-rails<br>73 mm                         |
| Width of side-rails<br>25 mm | Max. load capacity<br>150 kg                              | Design type<br>To lean against    | Transport dimensions<br>(plus packaging)<br>4720 x 425 x 75 mm,<br>9 kg | Business division<br>MUNK Günzburger<br>Steigtechnik |
| Order no.<br>010016          |                                                           |                                   |                                                                         |                                                      |

## Facts

- Aluminium rung straight ladder
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Rung distance: 280 mm

- Ladder width: 420 mm (without stabiliser)
- nivello® ladder shoes with patented 2-axis inclination technology
- Maximum load: 150 kg
- Note: Straight ladders over 3.0 m can be used without a stabiliser only when they are used exclusively for their intended purpose (e.g. permanently installed, fitted with hooks, fastened with a belt)

### Scope of supply

- Ladder: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---

## Added value

---

The movable ladder shoe sets new standards in stability

[Learn more](#)



Retrofit stabiliser

Safe, standards-compliant ascent

- For retrofitting existing ladders with ladder lengths over 3.0 m in compliance with standards
- Non-slip ladder shoes
- Available in different widths



Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



Corporate certifications

Standards for quality and sustainability

