



Order no.: 011111

# Multi-function ladder 4section with nivello® stabiliser



Number of rungs

2x2 + 2x3 2x3 + 2x4

## Specification

Working height 5.85 m	Step design Rungs	Number of steps/rungs 4x 4 rungs	Step/Rung height 30 mm	Step depth 30 mm
Step/Rung distance 280 mm	Ladder length as straight ladder 4.75 m	Ladder length as double- sided ladder 2.3 m	Base spread as double ladder 1.55 m	Inclination 70 °
Outer width 350 mm	Stabiliser width 930 mm	Depth of side-rails 58 mm	Width of side-rails 25 mm	Max. load capacity 150 kg
Transport dimensions 1229 x 360 x 263 mm, 15.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 011111		

#### **Facts**

- Aluminium multi-function rung ladder
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Can be used as a step and straight ladder



- Optimum operational safety due to six automatically locking steel hinges
- nivello® stabilisers for extra safe stance and ascent (double-sided, enclosed separately)

Rung distance: 280 mm

Ladder width: 350 mm

Maximum load: 150 kg

 Note: In accordance with DIN EN 131-4 it cannot be used in the working trestle and wall clearance position

## Scope of supply

Ladder: 1 x

Stabiliser (enclosed separately): 2 x

Instructions for use and operation: 1 x

#### Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality



- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures









#### Added value

#### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



## Easy handling

- Insertion hooks with lift-off protection or automatically locking steel hinges
- Optimised guidance, thanks to guide fixtures with high-strength plastic coating

#### Flexibility

- Universal and versatile use
- Compact size for transport and storage
- Upper ladder can also be used individually (up to 3.0 m)



The movable ladder shoe sets new standards in stability





## Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



#### nivello® stabiliser

Extra safe, standards-compliant ascent for straight ladders over 3.0 m

- Extra wide stabiliser for even greater stability
- nivello® ladder shoes with patented 2-axis inclination technology, integrated work angle check and exchangeable foot plates
- Individually available as spare part





#### roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



#### Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on <u>TRBS 2121 Part 2</u> has been summarised on our Service page
- Read our <u>tips and tricks</u> on how to calculate <u>working height</u>





## Corporate certifications

## Standards for quality and sustainability









