



Order no.: 021218

2-section rung ropeextension ladder without stabiliser



Number of rungs

2x14 2x16 2x18 2x20

Specification

Working height	Step design	Number of steps/rungs	Step/Rung height	Step depth
10.3 m	Rungs	2x 18 rungs	30 mm	30 mm
Step/Rung distance	Retracted length 5.3 m	Extended length	Outer width	Depth of side-rails
280 mm		9.18 m	420 mm	98 mm
Width of side-rails 25 mm	Design type To lean against 2- part	Transport dimensions 5290 x 445 x 205 mm, 32.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 021218

Facts

- Rung rope-extension ladder made of aluminium
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Convenient height adjustment from rung to rung thanks to two pulleys with plastic cable
- Upper ladder with wall wheels



- Corrosion-resistant guide fixtures with sliding guides
- Rung distance: 280 mm
- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg
- Note: Straight ladders over 3.0 m can be used without a stabiliser only when they are used exclusively for their intended purpose (e.g. permanently installed, fitted with hooks, fastened with a belt)
- nivello® ladder shoes with patented 2-axis inclination technology

Scope of supply

Ladder: 1 x

Instructions for use and operation: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality



- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures









Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



The movable ladder shoe sets new standards in stability



Optimum and smooth operation, thanks to easily accessible elements

- Simple height adjustment from rung to rung or from step to step
- Wall wheels on the upper part (from 14 rungs or more)
- Fittings with sliding guides
- Smooth-running rope pulley



Retrofit stabiliser

Safe, standards-compliant ascent

- For retrofitting existing ladders with ladder lengths over 3.0 m in compliance with standards
- Non-slip ladder shoes
- Available in different widths





Corporate certifications

Standards for quality and sustainability









