



Order no.: 027928

Entry frame 135/196

Number of rungs

7

Specification

Length 2.08 m	Height 1.96 m	Scaffolding width 1.35 m	Suitable for Rollgerüste	Transport dimensions (plus packaging) 2080 x 1340 x 60 mm, 9.5 kg
Business division MUNK Günzburger Steigtechnik	Order no. 027928			

Facts

- Easy to install thanks to sophisticated push-fit system
- Supports efficient and safe working
- For scaffolding width 1.35m

Scope of supply

- Frame: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

Standards for quality and sustainability



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548



Nachhaltigkeit
EcoVadis sustainable supply management
CSR-Rating in Silber 2022

