MUNK
Sicherheit. Made in Germany.



Order no.: 033120

Roof ladder wood

Number of rungs

10 | 12 | 14 | 16 | 18

Specification

Ladder length 2.8 m	Number of steps/rungs 10 rungs	Step/Rung distance 280 mm	Outer width 350 mm	Depth of side-rails 29 mm
Design type For hanging	Transport dimensions (plus packaging) 2800 x 350 x 65 mm, 6.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 033120	

Facts

- For installation on roof pitches from 22.5° to 75° and for load distribution during roofing work according to standard DIN 4567-4
- Caroline pine or finger-jointed pine side-rails with bevelled ends for easy handling
- Side-rails with strong, upwardly curved rungs; waterproof glued, weatherproof glazed and screwed 4 times per rung
- Ladder width: 350 mm
- Rung distance: 280 mm

- Note: In accordance with German Social Accident Insurance (DGUV) information sheet 201-054, roof ladders must be suspended in safety roof hooks as per DIN EN 517 (not in the top rung). Use as a straight ladder is not permitted

Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

