



Order no.: 033220

# Double-sided rung ladder wood



Number of rungs

## Specification

Working height 4.2 m	Step design Rungs	Number of steps/rungs 2x 10 rungs	Step/Rung distance 280 mm	Height 2.72 m
Ladder length 2.91 m	Base spread 1.5 m	Lower outer width 680 mm	Upper outer width 380 mm	Depth of side-rails 60 mm
Max. load capacity 150 kg	Design type Freestanding   Double-sided access	Transport dimensions 2910 x 670 x 123 mm, 17.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 033220

#### **Facts**

- Double-sided rung ladder made of wood
- Side-rails made of finger-jointed pine or knotfree Caroline pine, rungs made of ash
- Pegged rung-to-side-rail connection, resulting in smooth side-rail surface
- Sturdy steel hinges
- Supplied as standard with practical bucket hook
- Spreader lock with two galvanized steel chains
- Rung distance: 280 mm



- Maximum load: 150 kg
- These products are covered by the statutory warranty

## Scope of supply

Ladder: 1 x

#### Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users



## More product pictures





Added value

#### Industrial grade

- Sturdy processing for demanding applications (e.g. 4-fold edging)
- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories

#### Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on <u>TRBS 2121 Part 2</u> has been summarised on our Service page
- Read our <u>tips and tricks</u> on how to calculate <u>working height</u>





## Corporate certifications

## Standards for quality and sustainability









