



Order no.: 033310

Multi-purpose ladder, 3-part, with nivello® crossbar and wall rollers



Number of rungs

3x6

3x8

3x10

3x12

3x14

Specification

| | | | | |
|------------------------------|---|---|---|---|
| Working height 8 m | Step design Rungs | Number of steps/rungs 3x 10 rungs | Step/Rung height 30 mm | Step depth 30 mm |
| Step/Rung distance 280 mm | Ladder length, two-part, straight 5.03 m | Ladder length, three-part, straight 6.99 m | Ladder length, 2-part, double-sided with attachable section 4.93 m | Base spread as double ladder 2.07 m |
| Inclination 70 ° | Retracted length 3.06 m | Length of ladder sections 3.06 m | Outer width 490 mm | Stabiliser width 1.2 m |
| Depth of side-rails 73 mm | Width of side-rails 25 mm | Max. load capacity 150 kg | Transport dimensions (plus packaging) 3040 x 505 x 200 mm, 24 kg | Business division MUNK Günzburger Steigtechnik |
| Order no. 033310 | | | | |

Facts

- Multi-purpose rung ladder made from aluminium
- Stable rectangular tube side-rails

- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Can be used as a step ladder, straight ladder and push-up extension ladder
- Suitable for stairs with ladder length up to 3.0 m
- Simple height adjustment from rung to rung thanks to insertion hook with automatically engaging lift-off protection
- Upper ladder with wall wheels
- nivello® ladder shoes and nivello® stabiliser (enclosed separately)
- Spreader lock with two high-strength polyester straps and detachable metal strut
- Rung distance: 280 mm
- Ladder width: 490 mm (without stabiliser)
- Maximum load: 150 kg

Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x
- Instructions for use and operation: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification

- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Flexibility

- Universal and versatile use
- Compact size for transport and storage
- Upper ladder can also be used individually (up to 3.0 m)



The movable ladder shoe sets new standards in stability

[Learn more](#)



Easy handling

- Insertion hooks with lift-off protection or automatically locking steel hinges
- Optimised guidance, thanks to guide fixtures with high-strength plastic coating

Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



nivello® stabiliser

Extra safe, standards-compliant ascent for straight ladders over 3.0 m

- Extra wide stabiliser for even greater stability
- nivello® ladder shoes with patented 2-axis inclination technology, integrated work angle check and exchangeable foot plates
- Individually available as spare part



roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



Corporate certifications

Standards for quality and sustainability

