



Order no.: 040114

Single-sided stepladder



Number of steps

- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 12
- 14

Specification

|                              |                                                           |                                                                           |                                                      |                              |
|------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------|------------------------------------------------------|------------------------------|
| Working height<br>5.25 m     | Step design<br>Steps                                      | Number of steps/rungs<br>14 steps                                         | Platform included as<br>step<br>Yes                  | Step depth<br>80 mm          |
| Step/Rung distance<br>235 mm | Type of non-slip<br>protection<br>Aluminium<br>corrugated | Height<br>3.92 m                                                          | Platform height<br>3.25 m                            | Base spread<br>2.4 m         |
| Inclination<br>70 °          | Lower outer width<br>800 mm                               | Depth of side-rails<br>73 mm                                              | Depth of side-rails,<br>support<br>58 mm             | Width of side-rails<br>25 mm |
| Max. load capacity<br>150 kg | Design type<br>Freestanding  <br>Single-sided access      | Transport dimensions<br>(plus packaging)<br>4185 x 777 x 164<br>mm, 18 kg | Business division<br>MUNK Günzburger<br>Steigtechnik | Order no.<br>040114          |

Facts

- Stepladder made of aluminium
- Stable rectangular tube side-rails
- 80 mm deep grooved steps and large platform
- 4-fold edged step-to-side-rail connection
- Conical side-rail guide for safe stance

- nivello® ladder shoes with patented 2-axis inclination technology
- ergo-pad® grip area with clamping mechanism
- 'safe-cap' ladder joint
- Practical storage tray with integrated hooks and tool holders
- From seven steps or more: Spreader lock with two high-strength polyester straps
- Step spacing: 235 mm
- Ladder inclination: 70°
- Available with and without step padding
- Maximum load: 150 kg

### Scope of supply

- Ladder: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality

- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

---

## Added value

---

### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



### Storage tray

- For the practical storage of small parts
- Made from high-quality plastic
- Partly with integrated hooks and tool holders
- Different versions, depending on the ladder model



### Ladder joint safe-cap

- Smooth ladder joint with large contact surface and sturdy plastic protective cap
- The 6 rivets and thicker wall thickness provide for greater stability and protection at this sensitive point on the ladder, increasing its service life
- The safe-cap protects the ladder when in use, when loading and storing, as well as the contact surfaces, walls, truck loading areas and the joint itself



The movable ladder shoe sets new standards in stability

[Learn more](#)



### ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point



#### Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



#### Certificates



Corporate certifications

Standards for quality and sustainability

