



Order no.: 041206

# Double-sided stepladder with castors



Number of steps

2x3	2x4	2x5	2x6	2x7	2x8	2x9	2x10
2x12	2						
2x14	ŀ						

# Specification

Working height 2.2 m	Step design Steps	Number of steps/rungs 2x 3 steps	Step depth 80 mm	Step/Rung distance 235 mm
Type of non-slip protection Aluminium corrugated	Height 670 mm	Base spread 690 mm	Inclination 70 °	Lower outer width 590 mm
Depth of side-rails 73 mm	Width of side-rails 25 mm	Castor diameter 80 mm	Max. load capacity 150 kg	Design type Freestanding   Double-sided access   With castors
Transport dimensions 747 x 588 x 200 mm, 7.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 041206		

# **Facts**

- Stepladder made of aluminium
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm
- 4-fold edged step-to-side-rail connection
- Conical side-rail guide for safe stance



- nivello® ladder shoes with patented 2-axis inclination technology
- Four self-locking spring-loaded castors (Ø 80 mm)
- Rigid connection through metal struts detachable on both sides

Step spacing: 235 mm

Ladder inclination: 70°

Maximum load: 150 kg

# Scope of supply

Ladder: 1 x

# Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard,
  small amounts of plastic
- No health hazards for the users



# More product pictures











## Added value

## Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



The movable ladder shoe sets new standards in stability

#### Learn more



## ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point



## Spring-loaded castors

- High stability, easy to change position
- Easy to move the ladder when it is set up
- Self-locking
- Also retrofittable and available as a spare part




## Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on <u>TRBS 2121 Part 2</u> has been summarised on our Service page
- Read our <u>tips and tricks</u> on how to calculate <u>working height</u>





# Certificates





# Corporate certifications

# Standards for quality and sustainability









