MUNK
Sicherheit. Made in Germany.



Order no.: 041206

Double-sided stepladder with castors

Number of steps

2x3 | 2x4 | 2x5 | 2x6 | 2x7 | 2x8 | 2x9 | 2x10 | 2x12 | 2x14

Specification

Working height 2.2 m	Step design Steps	Number of steps/rungs 2x 3 steps	Step depth 80 mm	Step/Rung distance 235 mm
Type of non-slip protection Aluminium corrugated	Height 670 mm	Base spread 690 mm	Inclination 70 °	Lower outer width 590 mm
Depth of side-rails 73 mm	Width of side-rails 25 mm	Castor diameter 80 mm	Max. load capacity 150 kg	Design type Freestanding | Double-sided access | With castors
Transport dimensions (plus packaging) 747 x 588 x 200 mm, 7.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 041206		

Facts

- Stepladder made of aluminium
- Stable rectangular tube side-rails
- 80 mm deep, ribbed steps R10
- 4-fold edged step-to-side-rail connection
- Conical side-rail guide for safe stance

- nivello® ladder shoes with patented 2-axis inclination technology
- Four self-locking spring-loaded castors (Ø 80 mm)
- Rigid connection through metal struts detachable on both sides
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg

Scope of supply

- Ladder: 1 x

More product pictures







Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



The movable ladder shoe sets new standards in stability

Learn more



ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point



Spring-loaded castors

- High stability, easy to change position
- Easy to move the ladder when it is set up
- Self-locking
- Also retrofittable and available as a spare part



Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on TRBS 2121 Part 2 has been summarised on our Service page
- Read our tips and tricks on how to calculate working height



Certificates



25KFP0049-01 - Test Certificate "Bauart geprüft"

Valid in

DIN EN 131-1:2019
DIN EN 131-2:2017
DIN EN 131-3:2018
EK5/AK1 17-02.4:2021
PAK-ANFORDERUNG FÜR GS (PAH REQUIREMENT FOR GS) AFPS GS 2019:01 PAK

MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022