

Order no.: 041406

Step shelf ladder, mobile



Number of steps

- 6
- 8
- 10
- 12
- 14
- 16
- 18



Specification

|                                                      |                                   |                                  |                                     |                                                                             |
|------------------------------------------------------|-----------------------------------|----------------------------------|-------------------------------------|-----------------------------------------------------------------------------|
| Working height<br>2.8 m                              | Step design<br>Stufen             | Number of steps/rungs<br>6 steps | Step width<br>370 mm                | Step depth<br>80 mm                                                         |
| Step/Rung distance<br>235 mm                         | Vertical hook-in height<br>1.92 m | Ladder length<br>1.69 m          | Base area<br>780 mm                 | Inclination<br>70 °                                                         |
| Outer width<br>420 mm                                | Castor diameter<br>80 mm          | Max. load capacity<br>150 kg     | Design type<br>Fahrbar   Mit Rollen | Transport dimensions<br>(plus packaging)<br>1860 x 600 x 110<br>mm, 8.38 kg |
| Business division<br>MUNK Günzburger<br>Steigtechnik | Order no.<br>041406               |                                  |                                     |                                                                             |

Facts

- Step shelf ladder made of aluminium
- Stable rectangular tube side-rails
- 80 mm deep, ribbed steps R10
- 4-fold edged step-to-side-rail connection
- Easy to move thanks to smooth-running undercarriage at the upper end

- Compact to store when not in use
- Self-locking spring-loaded castors, Ø 80 mm, at the lower end
- Non-slip ladder shoes
- Step spacing: 235 mm
- Ladder width: 420 mm (without castors)
- Ladder width with castors: 600 mm
- Ladder inclination: 70°
- Maximum load: 150 kg
- Note: Shelf ladders are manufactured in standard lengths stated here as well as individually made to measure. Please indicate the exact vertical hook-in height – the price includes the next higher ladder and a flat rate for changes of 51.00 euros RRP excluding VAT. Shelf ladders made to size are non-returnable

### Scope of supply

- Instructions for use and operation: 1 x
- Ladder: 1 x
- Spring-loaded castor: 2 x

### More product pictures



## Added value

---

### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



### Rail system

- Made-to-measure production of the rail system
- Easy assembly of all components



### Versatile solutions


- Ladders available in standard lengths or individual dimensions
- Available with and without roll-top as well as a rotatable version
- Optional spring-loaded castors
- For single and double-sided shelves



### clip-step step padding

Optimised and certified non-slip protection for greater comfort and safety


- Made of grooved plastic
- Exact fit and easy to clip onto the steps
- Applied up to the maximum accessible step as a visual check
- Retrofittable and available as spare part



### clip-step R 13 step padding

Certified non-slip protection for step ladders

- Fulfils the requirements of the highest possible non-slip class R 13 thanks to aluminium oxide particles
- Improves work safety in wet and oil-contaminated environments
- Applied up to the maximum accessible step as a visual check
- Retrofittable, available as a spare part and also in yellow in selected lengths (RAL 1021)



Corporate certifications

Standards for quality and sustainability

