MUNK
Sicherheit. Made in Germany.



Order no.: 051084

# Platform ladder with castors and handle

Number of steps

4 | 5 | 6 | 7 | 8 | 9 | 10

## Specification

| | | | | |
|---|---|---|---|---|
| Working height<br>2.9 m | Step design<br>Steps | Number of steps/rungs<br>4 steps | Platform included as step<br>Yes | Platform height<br>900 mm |
| Step depth<br>80 mm | Step/Rung distance<br>235 mm | Height<br>1.65 m | Base spread<br>1.16 m | Inclination<br>70 ° |
| Lower outer width<br>610 mm | Depth of side-rails<br>73 mm | Depth of side-rails, support<br>58 mm | Width of side-rails<br>25 mm | Castor diameter<br>125 mm |
| Max. load capacity<br>150 kg | Design type<br>Freestanding \| Single-sided access \| With castors | Transport dimensions (plus packaging)<br>1751 x 605 x 180 mm, 13 kg | Business division<br>MUNK Günzburger Steigtechnik | Order no.<br>051084 |

## Facts

- Platform ladder made of aluminium
- Stable rectangular tube side-rails
- 80 mm deep, ribbed steps R10
- Large, trapeze-shaped platform (400 / 360 x 425 mm)
- 4-fold edged step-to-side-rail connection



We reserve the right to make technical changes and price changes.

- Conical side-rail guide for safe stance
- Two handrails for safe ascent and descent (enclosed separately)
- 'safe-cap' ladder joint
- nivello® ladder shoes with patented 2-axis inclination technology
- Practical storage tray (350 x 200 mm)
- Rigid connection through metal struts detachable on both sides
- Spreader lock with two high-strength polyester straps
- Two lifting rollers Ø 125 mm and handles (supplied loose)
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg

## Scope of supply

- Ladder: 1 x
- Handrail (enclosed separately): 2 x
- Lifting castors: 2 x
- Instructions for use and operation: 1 x

## More product pictures







## Added value

Ladder joint safe-cap

- Smooth ladder joint with large contact surface and sturdy plastic protective cap
- The 6 rivets and thicker wall thickness provide for greater stability and protection at this sensitive point on the ladder, increasing its service life
- The safe-cap protects the ladder when in use, when loading and storing, as well as the contact surfaces, walls, truck loading areas and the joint itself



The movable ladder shoe sets new standards in stability

Learn more



## Certificates



25KFP0610-01 - Test Certificate "Bauart geprüft"

Valid in

DIN EN 131-1:2019
DIN EN 131-2:2017
DIN EN 131-3:2018
EK5/AK1 17-02.4:2021
PAK-ANFORDERUNG FÜR GS (PAH REQUIREMENT FOR GS) AFPS GS 2019:01 PAK

# Corporate certifications

## Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022