



Order no.: 051084

Platform ladder with castors and handle



Number of steps

- 4
- 5
- 6
- 7
- 8
- 9
- 10

Specification

Working height 2.9 m	Step design Stufen	Number of steps/rungs 4 steps	Platform included as step Ja	Platform height 900 mm
Step depth 80 mm	Step/Rung distance 235 mm	Height 1.65 m	Base spread 1.16 m	Inclination 70 °
Lower outer width 610 mm	Depth of side-rails 73 mm	Depth of side-rails, support 58 mm	Width of side-rails 25 mm	Castor diameter 125 mm
Max. load capacity 150 kg	Design type Freistehend Einseitig begehbar Mit Rollen	Transport dimensions (plus packaging) 1751 x 605 x 180 mm, 13 kg	Business division MUNK Günzburger Steigtechnik	Order no. 051084

Facts

- Platform ladder made of aluminium
- Stable rectangular tube side-rails
- 80 mm deep, ribbed steps R10
- Large, trapeze-shaped platform (400 / 360 x 425 mm)
- 4-fold edged step-to-side-rail connection

- Conical side-rail guide for safe stance
- Two handrails for safe ascent and descent (enclosed separately)
- 'safe-cap' ladder joint
- nivello® ladder shoes with patented 2-axis inclination technology
- Practical storage tray (350 x 200 mm)
- Rigid connection through metal struts detachable on both sides
- Spreader lock with two high-strength polyester straps
- Two lifting rollers Ø 125 mm and handles (supplied loose)
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg

Scope of supply

- Ladder: 1 x
- Handrail (enclosed separately): 2 x
- Lifting castors: 2 x
- Instructions for use and operation: 1 x

More product pictures



Added value

Ladder joint safe-cap

- Smooth ladder joint with large contact surface and sturdy plastic protective cap
- The 6 rivets and thicker wall thickness provide for greater stability and protection at this sensitive point on the ladder, increasing its service life
- The safe-cap protects the ladder when in use, when loading and storing, as well as the contact surfaces, walls, truck loading areas and the joint itself



The movable ladder shoe sets new standards in stability

[Learn more](#)



Certificates



25KFP0610-01 -
Test Certificate
"Bauart geprüft"

Valid in

DIN EN 131-1:2019
DIN EN 131-2:2017
DIN EN 131-3:2018
EK5/AK1 17-
02.4:2021
PAK-
ANFORDERUNG
FÜR GS (PAH
REQUIREMENT
FOR GS) AFPS GS
2019:01 PAK

Corporate certifications

Standards for quality and sustainability

