



Order no.: 063013

Shaft ladder, V4A
stainless steel, 400 mm
clear width

Number of rungs

4	5	6	7	8	9	10	11	12
13	14	15						

Specification

Clear width 400 mm	Ladder length 3.64 m	Number of steps/rungs 13 rungs	Step depth 30 mm	Depth of side-rails 50 mm
Width of side-rails 20 mm	Outer width 440 mm	Max. load capacity 150 kg	Material Stainless steel V4A	Transport dimensions (plus packaging) 3640 x 440 x 50 mm, 18 kg
Business division MUNK Günzburger Steigtechnik	Order no. 063013			

Facts

- Cured and passivated
- Clear width 400 mm
- Rectangular tube side-rails, 50 x 20 mm
- Non-slip perforated rungs
- Various wall anchors available as accessories

Scope of supply

- Ladder: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Rational modular principle

- Shaft ladders in two widths and various lengths offer the right solution for every project
- Ideal for sewage treatment plants, landfills, retention basins, pump shafts, etc.
- Each individual component in the modular kit system meets the same quality and efficiency requirements
- Use of fall protection with wide design possible



Mounting and fastening

- Quick and easy installation of the shaft ladders thanks to the optimised installation system
- Adjustable wall anchors for complex projects additionally facilitate installation
- Suitable accessories available for the different material versions



Highest quality

- Stable rectangular tube side-rails
- High-strength rung-to-side-rail connection
- Non-slip perforated rungs




Various material versions

- Depending on the application, shaft ladders made of steel, stainless steel and reinforced fibre glass are available
- Wall anchors and accessories are also available in several materials



Entry aids

- Different variants in accordance with DIN standards and German Social Accident Insurance (DGUV) regulations for safe entry and exit
- Available in various materials to match the ladders



Certificates



24KFP1133-01 -
Test Certificate
"Bauart geprüft"

Valid in

DIN EN 14396:2004

Corporate certifications

Standards for quality and sustainability

