



Order no.: 063049

Exit side-rail angled

Material

Aluminium Anodised aluminium

Stainless steel Galvanised steel

Specification

| | | | | |
|-----------------|----------------------------|---|--|---------------------|
| Length 1.6 m | Material Stahl verzinkt | Transport dimensions (plus packaging) 1585 x 500 x 25 mm, 4.5 kg | Business division MUNK Günzburger Steigtechnik | Order no. 063049 |
|-----------------|----------------------------|---|--|---------------------|

Facts

- Single-sided, angled
- Side-rail dimensions: 60 x 25 mm
- Total length: 1,600 mm
- Working length: 1,200 mm
- 1 PU = 1 pcs.

Scope of supply

- Exit rail: 1 x
- Installation material: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001

- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Optimum planning

- Practical planning aids (available as [Downloads](#)) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



Corporate certifications

Standards for quality and sustainability

