



# Wall anchor U-bracket, rigid

Wall clearance [mm]



200



### Specification

Wall distance 150 mm	Wall anchor U-bracket	Material Galvanised steel	Transport dimensions 535 x 210 x 60 mm, 2.5 kg	Business division MUNK Günzburger Steigtechnik
Order no. 063257				

#### **Facts**

- Optimum stability thanks to rigid design
- Good anchoring for different wall types
- Steel quality ensures a high load-bearing capacity
- Wall anchor

## Scope of supply

■ Wall anchor: 1 x



#### Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

#### More product pictures





#### Added value

#### Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning





## Corporate certifications

#### on sustainability criteria







