



Order no.: 064006

Shaft ladder, glass fibre  
reinforced plastic,  
300 mm clear width

Number of rungs

|    |    |    |   |   |   |    |    |    |
|----|----|----|---|---|---|----|----|----|
| 4  | 5  | 6  | 7 | 8 | 9 | 10 | 11 | 12 |
| 13 | 14 | 15 |   |   |   |    |    |    |

Specification

|                       |                              |                                  |                                                     |                                                      |
|-----------------------|------------------------------|----------------------------------|-----------------------------------------------------|------------------------------------------------------|
| Clear width<br>300 mm | Ladder length<br>1.68 m      | Number of steps/rungs<br>6 rungs | Depth of side-rails<br>58 mm                        | Width of side-rails<br>25 mm                         |
| Outer width<br>350 mm | Max. load capacity<br>150 kg | Material<br>GFRP                 | Transport dimensions<br>1685 x 358 x 58 mm,<br>4 kg | Business division<br>MUNK Günzburger<br>Steigtechnik |
| Order no.<br>064006   |                              |                                  |                                                     |                                                      |

Facts

- Clear width 300 mm
- Rectangular side-rails 58 × 25 mm
- Grooved rungs
- Various wall anchors available as accessories

## Scope of supply

- Ladder: 1 x

## Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### Rational modular principle

- Shaft ladders in two widths and various lengths offer the right solution for every project
- Ideal for sewage treatment plants, landfills, retention basins, pump shafts, etc.
- Each individual component in the modular kit system meets the same quality and efficiency requirements
- Use of fall protection with wide design possible



### Mounting and fastening

- Quick and easy installation of the shaft ladders thanks to the optimised installation system
- Adjustable wall anchors for complex projects additionally facilitate installation
- Suitable accessories available for the different material versions



### Highest quality

- Stable rectangular tube side-rails
- High-strength rung-to-side-rail connection
- Non-slip perforated rungs



### Various material versions

- Depending on the application, shaft ladders made of steel, stainless steel and reinforced fibre glass are available
- Wall anchors and accessories are also available in several materials



### Entry aids

- Different variants in accordance with DIN standards and German Social Accident Insurance (DGUV) regulations for safe entry and exit
- Available in various materials to match the ladders



### Fiberglass

Ladders made of GFRP offer the perfect properties for special challenges. [Find out](#) what makes GFRP such a special material, how we use it for ladders and where these ladders are used.



# Certificates

---



24KFP1133-01 -  
Test Certificate  
"Bauart geprüft"

Valid in



DIN EN 14396:2004

## Corporate certifications

---

### Standards for quality and sustainability

