



Order no.: 065004

Entry aid, can be lowered (grab bar) with stainless steel sleeve

Material

Specification

Suitable for Shaft ladders

Transport dimensions 1455 x 95 x 190 mm, 4 kg

Business division MUNK Günzburger Steigtechnik Order no. 065004

Facts

- not for GRP shaft ladders
- Made of pickled and passivated V4A (1.4571) stainless steel or galvanised steel
- Can be lowered, for fastening to ladder side rails from 50 x 20 to 60 x 25 mm (not for reinforced fibre glass shaft ladders)

Scope of supply

■ Entry aid: 1 x

Assembly instructions: 1 x

Information on sustainability criteria

■ Corporate certification: ISO 9001



- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Corporate certifications

Standards for quality and sustainability









