MUNK
Sicherheit. Made in Germany.



Order no.: 115003

Scaling ladder push-fit section DIN EN 1147

Rung covering

Glow (yellow luminescent) | Standard (red)

Specification

Ladder length 780 mm	Ladder length, 4 scaling ladders 8.4 m	Outer width 485 mm	Ladder feet Ladder shoe	Depth of side-rails 74 mm
Width of side-rails 35 mm	Step/Rung height 28 mm	Step depth 29 mm	Number of steps/rungs 2 rungs	Step/Rung distance 273 mm
Max. load capacity 216 kg	Persons max. 2	Material Aluminium	Rung covering Standard (red)	Transport dimensions (plus packaging) 84 x 488 x 754 mm, 2.6 kg
Business division MUNK Rettungstechnik	Order no. 115003			

Facts

- T3 ladder section designed to slot into the recess in the top section, allowing it to be used either on its own or as the bottom ladder section
- Rescue ladder compliant with DIN EN 1147
- Made of aluminium
- Secure push-fit connections with spring-loaded locking pin

- Conical side-rail guide for safe stance
- Corrosion-resistant fixtures made of galvanised steel
- Permissible load: 216 kg / 2 people
- Side-rails and rungs made of high-strength aluminium
- With heat-insulating, non-slip plastic coating
- 4-fold edged rung-to-side-rail connection
- Non-slip and replaceable ladder shoes

More product pictures









MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022