



Order no.: 115701

Folding scaffolding
1.35x1.80m with
extension unit

Platform width [mm]

750

1350

Specification

Working height 3.48 m	Scaffolding length 1.88 m	Scaffolding width 1.44 m	Scaffolding height 2.66 m	Platform width 1.35 m
Platform length 1.8 m	Load capacity 1.5 kN/m ²	Transport dimensions (plus packaging) 1900 x 1400 x 650 mm, 69 kg	Indoor use, central installation möglich & zulässig	Outdoor use, central installation möglich & zulässig
Ballasting of scaffolding, outdoor, central installation 40 kg	Business division MUNK Günzburger Steigtechnik	Platform height 1.48 m		

Facts

- Mobile scaffolding made of sturdy round aluminium tubing with welded frame parts
- Folding frame made of rectangular tube side-rails with self-locking hinges
- Space-saving transport and storage
- Sturdy railing for safety railing
- Slip-resistant platform with large trapdoor for secure standing

- Four Ø 125 mm swivel castors with locking mechanisms
- Railing frame with horizontal struts for safety railing
- Delivered in assemblies. Once assembled, the scaffolding can be quickly set up and dismantled without tools
- Different platform widths available (0.75 / 1.35 m)
- Type-tested
- Load class/scaffolding group 2: 1.5 kN/m²
- Additional side boards for intermediate platforms are available as an option for country-specific requirements (e.g. Austria and France)

Scope of supply

- Folding frame unit with swivel castors: 1 x
- Push-fit frame 135/112: 2 x
- Platform with trapdoor: 1 x
- Platform without flap: 1 x
- Horizontal strut: 3 x

More product pictures



Added value

Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability




Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant



Expand your scaffolding with a safety railing (SG) and ensure reliable protection at work thanks to the system-integrated side protection! The retrofit reduces the risk of falling and enables the BG BAU work safety subsidy to be paid for up to 50% of the purchase costs (max. 100 euro per measure).

✓ Suitable for this product: Compatible SG safety railings offer effective side protection and are easy to retrofit.

All members of the BG BAU profit from this subsidy. This is intended to prevent accidents at work and improve ergonomics, especially on construction sites. All information from BG BAU can be found at:
www.bgbau.de/service/angebote/arbeitsschutzpraemien

A brief overview of the subsidy and an overview of our eligible products can be found on our website at [Knowledge](#).

Corporate certifications

Standards for quality and sustainability

